

**MOLYKOTE(R) 557 SILICONE DRY FILM
LUBRICANT (AEROSOL)**

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

SECTION 1. IDENTIFICATION

Product name : MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Product code : 000000000002412560

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Flammable aerosols : Category 1

Gases under pressure : Dissolved gas

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ systemic toxicity - single exposure : Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Precautionary Statements

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Hydrocarbon aerosol propellant

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 32 - <= 48
Naphtha, Petroleum, Light Alkylate	64741-66-8	>= 19 - <= 29
Propane	74-98-6	>= 12 - <= 18
Butane	106-97-8	>= 9 - <= 13
Propan-2-ol	67-63-0	>= 4 - <= 5

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|--|
| General advice | : | In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness. |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists. |
| Notes to physician | : | Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|---------------------------------------|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards during fire fighting | : | Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion prod- | : | Carbon oxides |

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
4.0	09/06/2017	653460-00007	Date of first issue: 10/21/2014

<p>Products</p> <p>Specific extinguishing methods</p> <p>Special protective equipment for fire-fighters</p>	<p>Silicon oxides Formaldehyde</p> <p>: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.</p> <p>: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.</p>
---	---

SECTION 6. ACCIDENTAL RELEASE MEASURES

<p>Personal precautions, protective equipment and emergency procedures</p> <p>Environmental precautions</p> <p>Methods and materials for containment and cleaning up</p>	<p>: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.</p> <p>: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.</p> <p>: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.</p>
--	--

SECTION 7. HANDLING AND STORAGE

<p>Technical measures</p> <p>Local/Total ventilation</p>	<p>: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.</p> <p>: Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust</p>
--	---

SAFETY DATA SHEET

DOW CORNING

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
 Date of first issue: 10/21/2014

ventilation.

Advice on safe handling : Do not get on skin or clothing.
 Do not breathe vapors or spray mist.
 Do not swallow.
 Do not get in eyes.
 Handle in accordance with good industrial hygiene and safety practice.
 Keep away from heat and sources of ignition.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.

Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Do not pierce or burn, even after use.
 Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	250 ppm 590 mg/m ³	NIOSH REL
Naphtha, Petroleum, Light Alkylate	64741-66-8	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
Propane	74-98-6	TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
Use only in an area equipped with explosion proof exhaust ventilation.
Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

**MOLYKOTE(R) 557 SILICONE DRY FILM
LUBRICANT (AEROSOL)**

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a dissolved gas
- Color : colorless
- Odor : solvent
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : Not applicable
-

**MOLYKOTE(R) 557 SILICONE DRY FILM
LUBRICANT (AEROSOL)**

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
4.0	09/06/2017	653460-00007	Date of first issue: 10/21/2014

Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Self-ignition	:	The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	0.8
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. Use at elevated temperatures may form highly hazardous compounds. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
4.0	09/06/2017	653460-00007	Date of first issue: 10/21/2014

temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Ingredients:

Acetone:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Naphtha, Petroleum, Light Alkylate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 7.6 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity : LD50 (Rabbit): > 2,200 - 2,500 mg/kg
Remarks: Based on data from similar materials

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min

**MOLYKOTE(R) 557 SILICONE DRY FILM
LUBRICANT (AEROSOL)**

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Test atmosphere: gas

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 72.6 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Ingredients:**Acetone:**

Assessment: Repeated exposure may cause skin dryness or cracking.

Naphtha, Petroleum, Light Alkylate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation

Propan-2-ol:

Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:**Acetone:**

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days
Method: OECD Test Guideline 405

Naphtha, Petroleum, Light Alkylate:

Species: Rabbit
Result: No eye irritation

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Propan-2-ol:

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

Acetone:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Naphtha, Petroleum, Light Alkylate:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Propan-2-ol:

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Hamster
Application Route: Intraperitoneal injection
Result: negative

Naphtha, Petroleum, Light Alkylate:

Genotoxicity in vitro : Test Type: Saccharomyces cerevisiae, gene mutation assay
(in vitro)

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Genotoxicity in vivo : Result: negative
: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Inhalation
Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:

Acetone:

Species: Mouse
Application Route: Skin contact
Exposure time: 1 Years
Result: negative

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

II

Naphtha, Petroleum, Light Alkylate:

Species: Mouse
Application Route: Skin contact
Exposure time: 102 weeks
Result: negative

Propan-2-ol:

Species: Rat
Application Route: inhalation (vapor)
Exposure time: 104 weeks
Method: OECD Test Guideline 451
Result: negative

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Result: negative

Naphtha, Petroleum, Light Alkylate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Inhalation
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Ingredients:

Acetone:

Assessment: May cause drowsiness or dizziness.

Naphtha, Petroleum, Light Alkylate:

Assessment: May cause drowsiness or dizziness.

Propane:

Assessment: May cause drowsiness or dizziness.

**MOLYKOTE(R) 557 SILICONE DRY FILM
LUBRICANT (AEROSOL)**

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Butane:

Assessment: May cause drowsiness or dizziness.

Propan-2-ol:

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Ingredients:****Acetone:**

Species: Rat
LOAEL: 1,700 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Naphtha, Petroleum, Light Alkylate:

Species: Rat
NOAEL: 10 mg/l
Application Route: inhalation (vapor)
Exposure time: 13 Weeks
Method: OPPTS 870.3465

Propane:

Species: Rat
NOAEL: 7.214 mg/l
Application Route: inhalation (gas)
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Butane:

Species: Rat
NOAEL: 9000 ppm
Application Route: inhalation (gas)
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Propan-2-ol:

Species: Rat
NOAEL: 5000 ppm
Application Route: inhalation (vapor)
Exposure time: 104 Weeks
Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

Ingredients:

Naphtha, Petroleum, Light Alkylate:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Acetone:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 6,210 - 8,120 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 1,106 - 2,212 mg/l Exposure time: 28 d

Naphtha, Petroleum, Light Alkylate:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 4.5 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 2.6 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

Propan-2-ol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

**MOLYKOTE(R) 557 SILICONE DRY FILM
LUBRICANT (AEROSOL)**

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

||

Persistence and degradability**Ingredients:****Acetone:**

|| Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Naphtha, Petroleum, Light Alkylate:

|| Biodegradability : Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Propane:

|| Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Butane:

|| Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Propan-2-ol:

|| Biodegradability : Result: rapidly degradable

Bioaccumulative potential**Ingredients:****Acetone:**

|| Partition coefficient: n-octanol/water : log Pow: -0.24

Naphtha, Petroleum, Light Alkylate:

|| Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Based on data from similar materials

Butane:

|| Partition coefficient: n-octanol/water : log Pow: 2.31

Propan-2-ol:

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
4.0	09/06/2017	653460-00007	Date of first issue: 10/21/2014

Partition coefficient: n-octanol/water : log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and Recovery Act (RCRA) : When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste.

Waste Code : D001: Ignitability

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
 Proper shipping name : AEROSOLS
 Class : 2.1
 Packing group : Not assigned by regulation
 Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950
 Proper shipping name : Aerosols, flammable
 Class : 2.1
 Packing group : Not assigned by regulation
 Labels : Flammable Gas
 Packing instruction (cargo aircraft) : 203
 Packing instruction (passenger aircraft) : 203

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0 Revision Date: 09/06/2017 SDS Number: 653460-00007 Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR
UN/ID/NA number : UN 1950
Proper shipping name : Aerosols

Class : 2.1
Packing group : Not assigned by regulation
Labels : FLAMMABLE GAS
ERG Code : 126
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetone	67-64-1	5000	12500

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Propan-2-ol 67-63-0 >= 4 - <= 5 %

US State Regulations**Pennsylvania Right To Know**

MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version 4.0	Revision Date: 09/06/2017	SDS Number: 653460-00007	Date of last issue: 05/02/2017 Date of first issue: 10/21/2014
----------------	------------------------------	-----------------------------	---

Acetone	67-64-1
Naphtha, Petroleum, Light Alkylate	64741-66-8
Propane	74-98-6
Butane	106-97-8
Propan-2-ol	67-63-0
Trimethylstearyloxysilane	18748-98-6

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

Acetone	67-64-1
Butane	106-97-8
Propan-2-ol	67-63-0

California Permissible Exposure Limits for Chemical Contaminants

Acetone	67-64-1
Propane	74-98-6
Butane	106-97-8
Propan-2-ol	67-63-0

The ingredients of this product are reported in the following inventories:

REACH	: For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
TSCA	: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
ENCS/ISHL	: All components are listed on ENCS/ISHL or exempted from inventory listing.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
PICCS	: All ingredients listed or exempt.
TCSI	: All ingredients listed or exempt.


MOLYKOTE(R) 557 SILICONE DRY FILM LUBRICANT (AEROSOL)

Version
4.0Revision Date:
09/06/2017SDS Number:
653460-00007Date of last issue: 05/02/2017
Date of first issue: 10/21/2014

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		4
PHYSICAL HAZARD		3

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-

**MOLYKOTE(R) 557 SILICONE DRY FILM
LUBRICANT (AEROSOL)**

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2017
4.0	09/06/2017	653460-00007	Date of first issue: 10/21/2014

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/06/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8